

REQUISITION FORM FOR NON-RETURN / CHECK VALVES

Please provide the requested information and fax to Schutte & Koerting at 215-639-1597 or email to sales@s-k.com

COMPANY NAME:	COMPANY NAME:			CONTACT:					
ADDRESS:	ADDRESS:			CITY, STATE, ZIP CODE:					
PHONE NUMBER:				FAX NUMBER:					
EMAIL:									
	LIVIAIL	•							
1. Applicable Specification				7. Design Condition					
☐ API 611 ☐ API	612	☐ ANSI 1	16.34	Max Pressu	ure	☐ psig ☐ Kg/cm²			
2. Prohibited Material				Max Temp]°F]°C
Copper				8. Operating Condition					
Restriction on Materials Procurement					MIN		MAX.		
Details:				Pressure] psig] Kg/cm²
				Temp] °F] °C
3. Valve Type				Flow] Lbs/hr] Kg/hr
☐ Non-Return Valve				9. Oil / Air Supply Condition					
☐ Closure Assist					MIN.		MAX.		
4. Closure Assist Cylinder				Pressure					psig
Air								L] Kg/cm ²
Oil				Temp] °F] °C
5. Valve Pressure Boundary Material Up to 750°F (ASTM 216 WCB)				10. Limit Switch					<u> </u>
751°F to 900°F (ASTM 217 WC6)				Quantity					
901°F to 1050°F (ASTM 217 WC9)				Type		П	Proximity		Limit
6. Valve Connections				Location			Open		Closed
	INLET	OUTL	.ET	Electrical C	ode				
Size			11. Additional Requirements						
Pressure Class									
Flange									
Weld Prep Pine Schedule									